



# KRØLL 2001



MODEL	K-70	K-160	K-180	K-220	K-260	K-320	K-420	K-560	K-100L	K-125L	K-200L
SPECIFICATIONS											
Max. jib length (m)	45	60	60	60	60	75	80	90	45	50	50
Min. jib length (m)	12	31	31	31	31	34	35	35	28	28	28
Min. reach (m)	2.1	2.9	2.9	3.3	3.3	3.3	3.5/5.0	3.5/5.0	4.0	4.5	5.0
Load (t) Reach (m)	1.2 45	1.8 60	2.3 60	3.0 60	3.5 60	3.2 75	3.5 80	2.5 90	2.0 45	2.0 50	3.5 50
Max. load (t) Max. reach (m)	5.0 12.7	10.0 14.4	10.0 18.1	12.0 19.6	12.0 21.7	16.0 20.0	30.0 17.6	30.0 21.1	6.0 17.0	8.0 13.0	10.0 25.0
Height under hook (standard mast) (m)	41	55	67	59	65	69	82	82	40	55	63
Standard mast dim. □ (m x m)	1.2	1.6	1.6	2.2	2.2	2.2	2.3	2.3	1.6	1.6	2.2
Floor climbing equipment	CS12	CS16	CS16	CL22	CL22	CL22	CL23	CL23	CS16	CS16	CL22
Telescopic equipment	CT12	CT16	CT16	CT22	CT22	CT22	CT23	CT23	CT16	CT16	CT22
Standard rail gauge (m)	4.5	6	6	6	6	6	9	9	6	6	6
Standard wind speed (m/s)											
In service	20	20	20	20	20	20	20	20	20	20	20
Out of service	42	42	42	42	42	42	42	42	42	42	42

The table above denotes the main characteristics of the production series for year 2001.  
It is for use as a guidance only, and can be adjusted to suit site requirements.

KRØLL Technical Services will provide you with a more defined load,  
reach, height specification to allow for a maximum load reach coverage at a minimum cost.

In addition to the above, quotations can be given for tower cranes of all ton-meter capacities up to 25000 tm.

## KRØLL CRANES A/S

Nordkranvej 2 . DK-3540 Lynge . Denmark . Phone: +45 48 18 74 00 . Fax: +45 48 18 88 07  
E-mail: krollcranes@krollcranes.dk . www.krollcranes.com

A MEMBER OF



MUHIBBAH ENGINEERING