



KRØLL MAXI RANGE



MODEL	K-800	K-1000	K-1400	K-1800	K-2500	K-3000	K-5000	K-10000	K-25000
SPECIFICATIONS									
Max. jib length (m)	78	78	80	80	90	90	90	82	100
Min. jib length (m)	42	42	42	42	42	48	48	60	60
Min. reach (m)	7	7	7	9	9	9	9	10	10
Load (t) Reach (m)	9.0 78	11.0 78	16.4 80	17.0 80	22.0 90	27.0 90	50.0 90	120.0 82	200.0 100
Max. load (t) Max. reach (m)	30.0 28	30.0 33	30.0 48	40.0 40	40.0 60	60.0 47	100.0 50	240.0 44	400.0 57
Height under hook (standard mast) (m)	84	78	72	60	72	60	90	84	100
Standard mast dim. □ (m x m)	3.2	3.2	4.0	4.0	5.0	5.0	8.0	8.0	10.0
Telescopic equipment	TS32	TS32	CT40	CT40	TS50	TS50	TS80	TS80	TS100
Standard rail gauge (m)	9	9	9	9	12	12	12	18	22
Portals (nominal rail gauge)	9	9	9	9	12	12	12	18	22
Standard wind speed (m/s)	In service	20	20	20	20	20	20	20	20
	Out of service	42	42	42	42	42	42	42	42

The listed cranes are a guide to the ton-meter range that KRØLL have designed and produced over the years.

FOR THE POSSIBILITIES OF MAKING HEAVY LIFTS

KRØLL CRANES A/S

Nordkranvej 2 . DK-3540 Lyngge . Denmark . Phone: +45 48 18 74 00 . Fax: +45 48 18 88 07
E-mail: krollcranes@krollcranes.dk . www.krollcranes.com

A MEMBER OF



MUHIBBAH ENGINEERING